

Accel-a-Writer[®]4G

Printing Solutions for Graphic Professionals

FEATURES

- 20 pages-per-minute
- Oversized 13" x 35.5" output
- High Speed Controller
- Adobe PostScript 3
- Up to 2400 x 2400 dpi
- Graphic Software Package including X-ACT and Densitometer Support

XANTÉ

CLEARLY™
Adobe

IMAGING

Accel-a-Writer® 4G Specifications

Print Speed	20 pages-per-minute (A4)*
Resolutions	1200 x 1200 dpi, 600 x 600 dpi (standard); 2400 x 2400 dpi (optional)*
Processor	IDT 79RC32355
Memory	Standard 64 MB SODIMM; expandable to 256 MB. Optional 63.5 mm (2.5") internal IDE drive
Toner Cartridge Life	Single Unit 14,000 sheets, (Letter/A4; 5% coverage)
Media Handling	Letter; legal; ledger; A3; A4; B4; B5; COM 10; Monarch; DL; C5; Executive 330 mm x 469 mm (322 mm x 468 mm print area); (13" x 18.5"; 12.69" x 18.42" print area); 330 mm x 635 mm (322 mm x 628 mm print area); (13" x 25", 12.69" x 24.72" print area); 330 mm x 901 mm** (322 mm x 895 mm print area); (13" x 35.5", 12.69" x 35.23" print area)
Special Stocks Media Weights	Approved label stock, transparencies, and envelopes 60 to 106 g/m ² (16 to 28 lbs) cassette tray 60 to 135 g/m ² (16 to 36 lbs) multipurpose feeder
Standard Input	500-sheet cassette and a 150-sheet multipurpose feeder
Optional Input	Optional media feeder for the addition of a 500-sheet cassette, (2 optional media feeders may be installed for a maximum of 1,650 sheets of input). Optional envelope cassette (capacity of 75)
Standard Output Duplexing	500 sheets maximum, face down Optional: A4/Letter; A3/279 mm x 431 mm
Dimensions	(W) 580 mm (22.8") (D) 602 mm (23.68") with cassette (H) 413 mm (16.24")
Weight	33.2 kg (73.3 lbs) - with cassette
Power Requirements	220-240 V ~ 50/60 Hz, 3.2 A
Noise Level	Printing - less than 49.5 dB; Standby - less than 35 dB
Printer Language	Adobe PostScript 3
Typefaces	136 resident PostScript Typefaces; TrueType 42 font rasterizer; Types 1, 3, 4, 5, and 6 PostScript download font support
Standard Interfaces	Simultaneously active – Parallel, USB***, 10/100BaseT Ethernet® (EtherTalk®, LPR, IPP, and TCP/IP)

All specs subject to change without notice.

Rev. 2/10/05

* Engine speed of 10 pages-per-minute at 2400 x 2400 dpi.

** Maximum paper size available is 330 mm x 635 mm at this resolution.

*** USB capability is also available for Win XP and 2K systems only.

FEATURES

Adobe PostScript 3 - True Adobe® PostScript® 3™ offers reliability, increased performance, and the assurance of compatibility to work from virtually any software application and hardware environment.

High Speed Controller - The IDT 79RC32355 processor coupled with XANTÉ's technology enables complex files to image incredibly fast.

X-ACT™ - XANTÉ's patented Accurate Calibration Technology gives you precise control over horizontal and vertical dimensions on page images, ensuring unmatched output accuracy.

Halftone Calibration Technology - This technology permits you to easily adjust the gamma curve of halftones. Users can calibrate midtones of halftone images to bring out lost detail from dark photos and to print at higher line screens.

Densitometer Support - Allows you to calibrate grayscales using a densitometer and utilities application to receive the highest accuracy possible from halftone images.

Enhanced Screening - This feature allows you to further fine tune output quality by providing 40% more levels of gray when needed.

Mirror Print - Allows you to output a job from any application so that the image is reversed from left to right providing right reading, emulsion side down output.

Negative Print - Provides the ability to output a negative image from any application regardless of job make-up.

Duplexing - Optional duplexing allows you to print on both sides of the page automatically. This can be used with page sizes up to 279 mm x 431 mm/A3. Duplexing requires an engine speed of 20 pages-per-minute; it is not available at 2400 x 2400 dpi.

Easy to Use Web Browser Interface - Enter the IP address of the printer in the address bar of your web browser to check its status, rename it, align paper, and much more.

Call XANTÉ Europe today for more information

+31-[0]26-3193210

Marketing 1, 6921 RE Duiven, The Netherlands

Fax +31-26-3193211

europe-sales@xante.com • europe-supplies@xante.com

(XANTÉ US) 251-473-6502 • Fax 251-473-6503

www.xante.com

© 2002 XANTÉ CORPORATION. XANTÉ, Accel-a-Writer, and X-ACT are trademarks or registered trademarks of XANTÉ CORPORATION. Adobe, PostScript, PostScript 3 and the Clearly Adobe Imaging and PostScript logos are trademarks or registered trademarks of Adobe Systems Incorporated. Other brands and product names are trademarks or registered trademarks of their respective holders. XANTÉ CORPORATION: Post Office Box 16526, Mobile, AL 36616-0526, USA, Tel. 251-473-6502, Fax: 251-473-6503, www.xante.com

